



Trimble DiNi

DIGITAL LEVEL

The Trimble® DiNi® Digital Level is a digital height measurement sensor from Trimble's Integrated Surveying™ portfolio of products. The Trimble DiNi is a field-proven tool designed for any job site where fast and accurate height determination is required. Use the Trimble DiNi for applications such as precise leveling of flat and sloping surfaces, establishing the vertical component of grade and ground profiles, subsidence monitoring, and establishing the vertical component of control networks.

UNEQUALLED FOR PERFORMANCE IN THE FIELD

The Trimble DiNi is designed to perform optimally every day, whatever your surveying job. It is built rugged—with a dust- and waterproof rating of IP55—to take the tough conditions of the job site in its stride. A backlight in the screen and a light in the circular bubble keep you productive even when daylight gets low.

The DiNi will operate for three days without requiring a battery change, then when it does just recharge it as you would your Trimble GNSS system battery...the batteries are the same to ensure convenience and productivity.

When a job is complete, easily transfer data from the instrument to a computer by using a USB storage device; You don't have to carry your instrument in to the office.

EASY TO LEARN, EASY TO USE

The Trimble DiNi Digital Level demands the industry's smallest measurement field—just 30 cm of code rod. So you can measure greater change in height between the level and the rod in one setup, and save time. Additionally, the small measurement area:

- ▶ reduces the number of stations needed by up to 20% because the Trimble DiNi is less impacted by a rod hidden by vegetation or hilly terrain.
- ▶ makes leveling in low light conditions, for example, in tunnels, easier because only a very small part of the staff needs to be illuminated.
- ▶ ensures greater accuracy through less influence of refraction near the ground.

The large graphical display of the Trimble DiNi is also unique, and is complemented by the latest Trimble keyboard for easy operation. Crew members used to operating other Trimble systems will easily adapt to the Trimble DiNi.

TRIMBLE QUALITY AND ACCURACY FOR MEASURING WITH CONFIDENCE

The Trimble DiNi Digital Level is designed to support the rest of Trimble's Integrated Surveying portfolio. The Trimble DiNi interface is based on Trimble's other advanced and field-proven controllers for easy adoption of the instrument by your crews. Proven Optics by Carl Zeiss ensure the Trimble DiNi offers the highest precision and best resolution.

Measure with confidence, knowing that with the Trimble DiNi Digital Level, your crew will obtain the best quality results with the highest level of productivity.

Key Features

- ▶ Determine accurate height information via a quick and easy key press
- ▶ Eliminate errors and reduce rework with digital readings
- ▶ Enjoy effortless data transfer between instrument and office
- ▶ Measure to a measurement field of just 30 cm
- ▶ Level 60% faster than with conventional automatic leveling



PERFORMANCE SPECIFICATIONS

Accuracy DIN 18723, standard deviation height measuring per 1 km of double leveling

Trimble DiNi 0.3 mm per km

Electronic measurement
 Invar precision bar code staff 0.3 mm
 Standard bar code staff 1.0 mm
 Visual measurement 1.5 mm
 Distance measurement with a 20 m sighting distance
 Invar precision bar code staff 20 mm
 Standard bar code staff 25 mm
 Visual measurements 0.2 m

Trimble DiNi 0.7 mm per km

Electronic measurement
 Invar precision bar code staff 0.7 mm
 Standard bar code staff 1.3 mm
 Visual measurement 2.0 mm
 Distance measurement with a 20 m sighting distance
 Invar precision bar code staff 25 mm
 Standard bar code staff 30 mm
 Visual measurement 0.3 m

Range

Electronic measurement 1.5 m–100 m
 Visual measurement from 1.3 m

Electronic measurement

Trimble DiNi 0.3 mm per km

Resolution height measurement 0.01 mm
 Resolution distance measurement 1 mm
 Measurement time 3 s

Trimble DiNi 0.7 mm per km

Resolution height measurement 0.1 mm
 Resolution distance measurement 10 mm
 Measurement time 2 s

Horizontal Circle

Type of graduation 400 grads and 360 deg
 Graduation interval 1 grad and 1 deg
 Estimation to 0.1 grad and 0.1 deg

Measurement Programs

Trimble DiNi 0.3 mm per km

Standard programs Single measurement with and without stationing, stakeout, line leveling with intermediate sight and stakeout, line adjustment
 Leveling methods¹ BF, BFFB, BFBF, BBFF, FBBF, aBF, aBFFB, aBFBF, aBBFF, aFBBF

Trimble DiNi 0.7 mm per km

Standard programs Single measurement with and without stationing, stakeout, line leveling with intermediate sight and stakeout
 Leveling methods BF, BFFB, aBF, aBFFB

ENVIRONMENTAL

Operating temperature -20 °C to +50 °C
 Dust- and waterproofing IP55

GENERAL SPECIFICATION

Telescope

Aperture 40 mm
 Field of view at 100 m 2.2 m
 Electronic measurement field 0.3 m
 Magnification
 Trimble DiNi 0.3 mm per km 32 x
 Trimble DiNi 0.7 mm per km 26 x

Compensator

Inclination range ±15'
 Setting accuracy
 Trimble DiNi 0.3 mm per km ±0.2"
 Trimble DiNi 0.7 mm per km ±0.5"
 Circular level 8/2 mm with illumination

Display Graphical, 240 x 160 pixels, monochrome with illumination

Keyboard 19-key alpha-numeric and 4-way arrow key for navigation

Recording

Internal memory up to 30 000 data lines
 External memory USB Flash Drive support
 Data transfer USB Interface for data transfer between DiNi and PC (means two way communication)

Real-time clock and temperature sensor

Trimble DiNi 0.3 mm per km Recording of time or temperature
 Trimble DiNi 0.7 mm per km N.A.

Power supply

Internal battery Li-Ion, 7.4 V / 2.4 Ah
 Operating time 3 days working time without illumination
 Weight (including battery) 3.5 kg

¹ F = Foresight, B = Backsight, a = alternating
 Certified quality in accordance with DIN ISO 9001/EN 29001.

Specifications subject to change without notice.



GE TEAM
 Autoriseret forhandler af Trimble®

Contact your local Trimble Authorised Distribution Partner for more information

NORTH AMERICA
 Trimble Inc.
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE
 Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC
 Trimble Navigation
 Singapore Pty Limited
 80 Marine Parade Road
 #22-06, Parkway Parade
 Singapore 449269
 SINGAPORE

